

PERFORMANCE DATA

MSL/MSLP

Duct Size	Neck Velocity (fpm)	300	400	500	600	700	800	900	1000
	Velocity Pressure (in. w.g.)	0.006	0.01	0.016	0.022	0.031	0.04	0.05	0.062
	Total Pressure (in. w.g.)	0.03	0.053	0.083	0.119	0.163	0.212	0.269	0.332
6 x 6	Flow Rate (cfm)	75	100	125	150	175	200	225	250
	Sound (NC)	-	-	-	-	16	20	23	27
	Throw (ft)	9-11-16	11-13-18	12-15-21	13-16-23	14-17-24	15-18-26	16-20-28	17-21-29
8 x 8	Flow Rate (cfm)	133	178	222	267	311	356	400	444
	Sound (NC)	-	-	-	-	18	22	26	29
	Throw (ft)	12-15-21	14-17-25	16-19-27	17-21-30	19-23-32	20-25-35	21-26-37	22-27-39
10 x 10	Flow Rate (cfm)	208	278	347	417	486	556	625	694
	Sound (NC)	-	-	-	15	20	24	27	31
	Throw (ft)	15-19-27	18-22-31	20-24-34	22-27-38	23-29-41	25-31-43	27-33-46	28-34-48
12 x 12	Flow Rate (cfm)	300	400	500	600	700	800	900	1000
	Sound (NC)	-	-	-	17	21	25	29	32
	Throw (ft)	18-23-32	21-26-37	24-29-41	26-32-45	28-34-49	30-37-52	32-39-55	34-41-58
14 x 14	Flow Rate (cfm)	408	544	681	817	953	1089	1225	1361
	Sound (NC)	-	-	-	18	23	27	30	33
	Throw (ft)	21-26-37	25-30-43	28-34-48	30-37-53	33-40-57	35-43-61	37-46-64	39-48-68
16 x 16	Flow Rate (cfm)	533	711	889	1067	1244	1422	1600	1778
	Sound (NC)	-	-	-	19	24	28	31	34
	Throw (ft)	25-30-42	28-35-49	32-39-55	35-42-60	37-46-65	40-49-69	42-52-74	45-55-78
18 x 18	Flow Rate (cfm)	675	900	1125	1350	1575	1800	2025	2250
	Sound (NC)	-	-	-	20	25	29	32	35
	Throw (ft)	28-34-48	32-39-55	36-44-62	39-48-68	42-52-73	45-55-78	48-59-83	50-62-87
20 x 20	Flow Rate (cfm)	833	1111	1389	1667	1944	2222	2500	2778
	Sound (NC)	-	-	16	21	25	29	33	36
	Throw (ft)	31-38-53	35-43-61	40-48-69	43-53-75	47-57-81	50-61-87	53-65-92	56-69-97
22 x 22	Flow Rate (cfm)	1008	1344	1681	2017	2353	2689	3025	3361
	Sound (NC)	-	-	16	22	26	30	34	37
	Throw (ft)	34-41-58	39-48-67	44-53-75	48-58-83	51-63-89	55-67-95	58-72-101	62-75-107
24 x 24	Flow Rate (cfm)	1200	1600	2000	2400	2800	3200	3600	4000
	Sound (NC)	-	-	17	22	27	31	34	37
	Throw (ft)	37-45-64	42-52-74	47-58-82	52-64-90	56-69-97	60-74-104	64-78-110	67-82-116
26 x 26	Flow Rate (cfm)	1408	1878	2347	2817	3286	3756	4225	4694
	Sound (NC)	-	-	18	23	28	31	35	38
	Throw (ft)	40-49-69	46-56-80	51-63-89	56-69-98	61-75-105	65-80-113	69-85-120	73-89-126
28 x 28	Flow Rate (cfm)	1633	2178	2722	3267	3811	4356	4900	5444
	Sound (NC)	-	-	18	24	28	32	36	39
	Throw (ft)	43-53-74	50-61-86	55-68-96	61-74-105	66-80-113	70-86-121	74-91-129	78-96-136
30 x 30	Flow Rate (cfm)	1875	2500	3125	3750	4375	5000	5625	6250
	Sound (NC)	-	-	19	24	29	33	36	39
	Throw (ft)	46-56-80	53-65-92	59-73-103	65-80-113	70-86-122	75-92-130	80-98-138	84-103-145

Performance Notes:

1. Tested in accordance with ASHRAE Standard 70-2006 "Method of Testing for Rating the Performance of Air Outlets and Inlets."
2. All pressures are in in. w.g.
3. NC values are based on a room absorption of 10 dB re 10⁻¹² watts and one grille.
4. Blanks "-" indicate an NC value less than 15.
5. Air flow is in cfm.
6. Throw values are measured in feet for terminal velocities of 150 fpm (minimum), 100 fpm (middle) and 50 fpm (maximum).
7. Throw data is based on supply air and room air being at isothermal conditions.
8. Corrections for return application: use listed NC; multiply listed total pressure by 1.3 to obtain negative static pressure.
9. Throw is based on wall mounting grille within 18 in. of ceiling, therefore ceiling effect is included in throw values.