

# PERFORMANCE DATA

## MSRRP - Supply

Size	Neck Velocity (fpm)	100	150	200	250	300	400	500	600	700
	Velocity Pressure (in. w.g.)	0.001	0.001	0.002	0.004	0.006	0.01	0.016	0.022	0.031
	Total Pressure (in. w.g.)	0.006	0.013	0.024	0.037	0.053	0.095	0.148	0.213	0.290
6 x 6	Flow Rate (cfm)	25	38	50	63	75	100	125	150	175
	Sound (NC)	-	-	-	-	-	-	21	29	35
	Throw (ft)	02-04-10	04-07-15	07-10-20	08-12-25	10-15-30	13-20-35	16-25-40	20-30-43	23-33-47
9 x 9	Flow Rate (cfm)	56	84	113	141	169	225	281	338	394
	Sound (NC)	-	-	-	-	-	16	25	33	40
	Throw (ft)	02-05-14	05-10-21	9-14-28	12-17-35	14-21-42	19-28-53	23-35-59	28-42-65	32-49-70
10 x 10	Flow Rate (cfm)	69	104	139	174	208	278	347	417	486
	Sound (NC)	-	-	-	-	-	17	26	34	41
	Throw (ft)	02-05-15	05-11-23	9-15-30	13-19-38	15-23-46	20-30-59	25-38-66	30-46-72	36-53-78
12 x 12	Flow Rate (cfm)	100	150	200	250	300	400	500	600	700
	Sound (NC)	-	-	-	-	-	19	28	36	43
	Throw (ft)	03-06-18	6-13-27	11-18-36	15-22-45	18-27-54	24-36-71	30-45-79	36-54-87	42-63-94
14 x 14	Flow Rate (cfm)	136	204	272	340	408	544	681	817	953
	Sound (NC)	-	-	-	-	-	20	30	38	44
	Throw (ft)	03-07-21	7-15-31	12-21-41	17-26-52	21-31-62	28-41-82	34-52-92	41-62-101	48-72-109
16 x 16	Flow Rate (cfm)	178	267	356	444	533	711	889	1067	1244
	Sound (NC)	-	-	-	-	-	22	31	39	46
	Throw (ft)	03-07-23	7-17-35	13-23-47	20-29-59	23-35-70	31-47-94	39-59-105	47-70-115	55-82-125
18 x 18	Flow Rate (cfm)	225	338	450	563	675	900	1125	1350	1575
	Sound (NC)	-	-	-	-	-	23	32	40	47
	Throw (ft)	04-08-26	8-19-39	15-26-52	22-33-65	26-39-78	35-52-105	44-65-119	52-78-130	61-92-140
20 x 20	Flow Rate (cfm)	278	417	556	694	833	1111	1389	1667	1944
	Sound (NC)	-	-	-	-	-	24	34	41	48
	Throw (ft)	04-09-29	9-20-43	16-29-58	24-36-72	29-43-87	39-58-116	48-72-132	58-87-144	67-101-156
22 x 22	Flow Rate (cfm)	336	504	672	840	1008	1344	1681	2017	2353
	Sound (NC)	-	-	-	-	-	25	35	42	49
	Throw (ft)	4-10-32	10-22-47	17-32-63	26-40-79	32-47-95	42-63-126	53-79-145	63-95-159	74-111-171
24 x 24	Flow Rate (cfm)	400	600	800	1000	1200	1600	2000	2400	2800
	Sound (NC)	-	-	-	-	-	26	35	43	50
	Throw (ft)	5-11-34	11-24-52	19-34-69	29-43-86	34-52-103	46-69-137	57-86-158	69-103-173	80-120-187
26 x 26	Flow Rate (cfm)	469	704	939	1174	1408	1878	2347	2817	3286
	Sound (NC)	-	-	-	-	-	27	36	44	51
	Throw (ft)	5-11-37	11-25-56	20-37-74	31-46-93	37-56-111	49-74-148	62-93-171	74-111-188	87-130-203
28 x 28	Flow Rate (cfm)	544	817	1089	1361	1633	2178	2722	3267	3811
	Sound (NC)	-	-	-	-	15	27	37	45	51
	Throw (ft)	5-12-40	12-27-60	21-40-80	33-50-100	40-60-120	53-80-159	66-100-184	80-120-202	93-139-218
30 x 30	Flow Rate (cfm)	625	938	1250	1563	1875	2500	3125	3750	4375
	Sound (NC)	-	-	-	-	16	28	38	46	52
	Throw (ft)	6-13-43	13-29-64	23-43-85	35-53-106	43-64-128	57-85-170	71-106-198	85-128-217	99-149-234

### Performance Notes:

1. Tested in accordance with ASHRAE Standard 70-2006 "Method of Testing for Rating the Performance of Air Outlets and Inlets."
2. Air flow is in cfm.
3. All pressures are in in. w.g.
4. Throw values are measured in feet for terminal Velocities of 150 fpm (minimum), 100 fpm (middle) and 50 fpm (maximum).
5. Throw data is based on supply air and room air being at isothermal conditions.
6. NC values are based on room absorption of 10 dB re 10<sup>-12</sup> Watts and one grille.
7. Blanks "-" indicate an NC value less than 15.

# PERFORMANCE DATA

## MSRRP - Return

Size	Neck Velocity (fpm)	100	150	200	250	300	400	500	600
	Velocity Pressure (in. w.g.)	0.001	0.001	0.002	0.004	0.006	0.010	0.016	0.022
	Neg. Static Pressure (in. w.g.)	0.008	0.017	0.031	0.048	0.070	0.124	0.193	0.278
6 x 6	Flow Rate (cfm)	25	38	50	63	75	100	125	150
	Sound (NC)	-	-	-	-	-	18	28	36
9 x 9	Flow Rate (cfm)	56	84	113	141	169	225	281	338
	Sound (NC)	-	-	-	-	-	23	32	40
10 x 10	Flow Rate (cfm)	69	104	139	174	208	278	347	417
	Sound (NC)	-	-	-	-	-	24	33	41
12 x 12	Flow Rate (cfm)	100	150	200	250	300	400	500	600
	Sound (NC)	-	-	-	-	-	26	35	43
14 x 14	Flow Rate (cfm)	136	204	272	340	408	544	681	817
	Sound (NC)	-	-	-	-	-	27	37	45
16 x 16	Flow Rate (cfm)	178	267	356	444	533	711	889	1067
	Sound (NC)	-	-	-	-	16	29	38	46
18 x 18	Flow Rate (cfm)	225	338	450	563	675	900	1125	1350
	Sound (NC)	-	-	-	-	17	30	39	47
20 x 20	Flow Rate (cfm)	278	417	556	694	833	1111	1389	1667
	Sound (NC)	-	-	-	-	19	31	41	48
22 x 22	Flow Rate (cfm)	336	504	672	840	1008	1344	1681	2017
	Sound (NC)	-	-	-	-	20	32	42	49
24 x 24	Flow Rate (cfm)	400	600	800	1000	1200	1600	2000	2400
	Sound (NC)	-	-	-	-	20	33	42	50
26 x 26	Flow Rate (cfm)	469	704	939	1174	1408	1878	2347	2817
	Sound (NC)	-	-	-	-	21	34	43	51
28 x 28	Flow Rate (cfm)	544	817	1089	1361	1633	2178	2722	3267
	Sound (NC)	-	-	-	-	22	34	44	52
30 x 30	Flow Rate (cfm)	625	938	1250	1563	1875	2500	3125	3750
	Sound (NC)	-	-	-	-	23	35	45	53

### Performance Notes:

1. Tested in accordance with ASHRAE Standard 70-2006 "Method of Testing for Rating the Performance of Air Outlets and Inlets."
2. All pressures are in in. w.g.
3. NC values are based on a room absorption of 10 dB re 10<sup>-12</sup> watts and one grille.
4. Blanks "-" indicate an NC value less than 15.
5. Air flow is in cfm.