



UNIT SIZE	L	W	A	B
9	15 1/2 (394)	17 1/2 (445)	10 (254)	3 13/16 (97)
10			12 (305)	
12			16 (406)	
14	19 (483)	30 (762)	21 (533)	5 5/16 (135)
16			38 (965)	

**STANDARD CONSTRUCTION:**

- 1/2" (13mm) THICK INTERNAL FIBERGLASS INSULATION WHICH MEETS REQUIREMENTS OF NFPA 90A AND UL181.
- 22 GAUGE GALVANIZED STEEL HOUSING. MECHANICALLY SEALED, LEAK RESISTANT CONSTRUCTION.
- RECTANGULAR DISCHARGE OPENING WITH SLIP AND DRIVE CLEAT DUCT CONNECTION.
- MULTI-POINT, CENTER AVERAGING AIRFLOW SENSOR.
- 1/2" (13mm) GALVANIZED DAMPER SHAFT WITH POSITION INDICATOR.
- RIGHT HAND UNIT SHOWN (CRH), LEFT HAND AVAILABLE.

**CONTROLS OPTIONS:**

- FIELD MOUNTED CONTROLS, SUPPLIED BY OTHERS (FLD)
- FACTORY MOUNTED DIGITAL CONTROLS, SUPPLIED BY OTHERS (FAC)

**CONTROLS SUPPLIED AND MOUNTED BY PRICE (EHP):**

- DIGITAL CONTROLS (DIG)
- PNEUMATIC CONTROLS (PNEU)

**UNIT OPTIONS:**

- NEMA1 CONTROLS ENCLOSURE (PS)
- DISCONNECT SWITCH (DSW)
- 20 GAUGE CASING (20GA)
- HANGER BRACKETS (HB)
- BRASS AIRFLOW SENSOR GAUGE TAPS (GT)

**BOTTOM ACCESS DOOR:**

- ACCESS DOOR WITH SCREWS (AD)
- ACCESS DOOR WITH SNAP LATCHES (ADL)
- ACCESS DOOR WITH QUARTER TURN LATCHES (ADQ)

**LINER OPTIONS:**

- FIBER FREE FOAM 1/2" (13mm) (FF50)
- FOIL FACED FIBERGLASS BOARD 5/8" (16mm) (FB)
- SOLID METAL WITH FG50 (SM50)
- CLEANROOM ANGLES WITH FB (CRAF)
- PERFORATED METAL WITH FB (AFPM)



ALL METRIC DIMENSIONS ( ) ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

<b>PROJECT:</b>		<b>PRICE</b>	<b>SDVLP</b> SINGLE DUCT TERMINAL VARIABLE VOLUME LOW PROFILE
<b>ENGINEER:</b>			
<b>CUSTOMER:</b>		274048	
<b>SUBMITTAL DATE:</b>	<b>SPEC. SYMBOL:</b>	06/14/2023	