

## PERFORMANCE DATA

### Performance Range

Performance	24 in. ACBL 2-Way Discharge	24 in. ACBL 1-Way Discharge	12 in. ACBL 2-Way Discharge	12 in. ACBL 1-Way Discharge
<b>Total Sensible Cooling</b> (Btu/h per Active Lineal Foot)	300 to 1,600	400 to 1,300	200 to 1,100	200 to 650
<b>Total Sensible Heating</b> (Btu/h per Active Lineal Foot)	500 to 2,000	550 to 1,750	350 to 950	350 to 800
<b>Sound Level</b>	NC < 15 to 35	NC < 15 to 35	NC < 15 to 35	NC < 15 to 35

### Design Parameters

Design Parameters	Cooling	Heating
<b>SAT</b>	55 – 65°F	60 – 90°F
<b>Airflow Rate</b>	3 – 25 cfm/ft. (2-Way Discharge) 3 – 15 cfm/ft. (1-Way Discharge)	
<b>EWT</b>	Dew point + 2°F	90 – 140°F
<b>Water ΔT</b>	2 – 6°F	10 – 20°F
<b>Water Flow Rate</b>	<b>min:</b> 0.5 gpm <b>max:</b> 3 gpm (Optimal ≥ 1 gpm)	
<b>Water ΔP</b>	0 – 10 ft.	
<b>Air ΔP</b>	0.2 – 0.8 in. (Target 0.4 – 0.6 in.)	