

PERFORMANCE DATA

80 / 81 / 82 / 80FF / 80FH - 0° Core

Core Area (sq. ft.)	Nominal Size	Core Velocity (fpm) Velocity Pressure (in. w.g.) Neg. Static Pressure (in. w.g.)	NC20								NC30			
			300	400	500	600	700	800	1000	1200	1400	1500		
			0.006	0.010	0.016	0.022	0.031	0.040	0.062	0.090	0.122	0.14		
0.15	7 x 4	Flow Rate (cfm)	45	60	75	90	105	120	150	180	210	225		
	6 x 5	Sound (NC)	-	-	-	-	-	-	22	28	34	37		
0.18	8 x 4	Flow Rate (cfm)	54	72	90	108	126	144	180	216	252	270		
	7 x 5	Sound (NC)	-	-	-	-	-	-	22	29	35	38		
0.22	10 x 4	Flow Rate (cfm)	66	88	110	132	154	176	220	264	308	330		
	8 x 5	Sound (NC)	-	-	-	-	-	-	23	30	36	38		
0.26	12 x 4	Flow Rate (cfm)	78	104	130	156	182	208	260	312	364	390		
	10 x 5	Sound (NC)	-	-	-	-	-	-	15	24	31	39		
0.30	14 x 4	Flow Rate (cfm)	90	120	150	180	210	240	300	360	420	450		
		Sound (NC)	-	-	-	-	-	-	16	24	31	40		
0.34	16 x 4	Flow Rate (cfm)	102	136	170	204	238	272	340	408	476	510		
	12 x 5	Sound (NC)	-	-	-	-	-	-	16	25	32	40		
0.39	18 x 4	Flow Rate (cfm)	117	156	195	234	273	312	390	468	546	585		
	14 x 5	Sound (NC)	-	-	-	-	-	-	17	25	32	41		
0.46	20 x 4	Flow Rate (cfm)	138	184	230	276	322	368	460	552	644	690		
	16 x 5	Sound (NC)	-	-	-	-	-	-	18	26	33	41		
0.52	24 x 4	Flow Rate (cfm)	156	208	260	312	364	416	520	624	728	780		
	18 x 5	Sound (NC)	-	-	-	-	-	-	18	26	33	42		
0.60	28 x 4	Flow Rate (cfm)	180	240	300	360	420	480	600	720	840	900		
	20 x 5	Sound (NC)	-	-	-	-	-	-	19	27	34	42		
0.69	30 x 4	Flow Rate (cfm)	207	276	345	414	483	552	690	828	966	1035		
	24 x 5	Sound (NC)	-	-	-	-	-	-	19	28	34	43		
0.81	36 x 4	Flow Rate (cfm)	243	324	405	486	567	648	810	972	1134	1215		
	28 x 5	Sound (NC)	-	-	-	-	-	-	20	28	35	43		
0.90	40 x 4	Flow Rate (cfm)	270	360	450	540	630	720	900	1080	1260	1350		
	30 x 5	Sound (NC)	-	-	-	-	-	-	20	29	35	44		
1.07	48 x 4	Flow Rate (cfm)	321	428	535	642	749	856	1070	1284	1498	1605		
	36 x 5	Sound (NC)	-	-	-	-	-	-	21	29	36	45		
1.18	34 x 6	Flow Rate (cfm)	354	472	590	708	826	944	1180	1416	1652	1770		
	24 x 8	Sound (NC)	-	-	-	-	-	-	21	30	37	45		
1.34	60 x 4	Flow Rate (cfm)	402	536	670	804	938	1072	1340	1608	1876	2010		
	48 x 5	Sound (NC)	-	-	-	-	-	-	22	30	37	45		
1.60	72 x 4	Flow Rate (cfm)	480	640	800	960	1120	1280	1600	1920	2240	2400		
	30 x 8	Sound (NC)	-	-	-	-	-	-	22	31	38	46		
1.80	60 x 5	Flow Rate (cfm)	540	720	900	1080	1260	1440	1800	2160	2520	2700		
	48 x 6	Sound (NC)	-	-	-	-	-	-	23	31	38	47		
2.08	72 x 5	Flow Rate (cfm)	624	832	1040	1248	1456	1664	2080	2496	2912	3120		
	60 x 6	Sound (NC)	-	-	-	-	-	-	23	32	39	47		
2.45	72 x 6	Flow Rate (cfm)	735	980	1225	1470	1715	1960	2450	2940	3430	3675		
	48 x 8	Sound (NC)	-	-	-	-	-	-	24	33	39	48		
2.78	36 x 12	Flow Rate (cfm)	834	1112	1390	1668	1946	2224	2780	3336	3892	4170		
	30 x 14	Sound (NC)	-	-	-	-	-	-	25	33	40	48		
3.11	60 x 8	Flow Rate (cfm)	933	1244	1555	1866	2177	2488	3110	3732	4354	4665		
	48 x 10	Sound (NC)	-	-	-	-	-	-	25	33	40	49		
3.61	72 x 8	Flow Rate (cfm)	1083	1444	1805	2166	2527	2888	3610	4332	5054	5415		
	60 x 10	Sound (NC)	-	-	-	-	-	-	26	34	41	49		
4.29	48 x 14	Flow Rate (cfm)	1287	1716	2145	2574	3003	3432	4290	5148	6006	6435		
	36 x 18	Sound (NC)	-	-	-	-	-	-	26	35	42	50		
4.65	72 x 10	Flow Rate (cfm)	1395	1860	2325	2790	3255	3720	4650	5580	6510	6975		
	48 x 16	Sound (NC)	-	-	-	-	-	-	27	35	42	50		
5.58	72 x 12	Flow Rate (cfm)	1674	2232	2790	3348	3906	4464	5580	6696	7812	8370		
	60 x 14	Sound (NC)	-	-	-	-	-	-	27	36	43	51		
6.25	72 x 14	Flow Rate (cfm)	1875	2500	3125	3750	4375	5000	6250	7500	8750	9375		
	60 x 16	Sound (NC)	-	-	-	-	-	-	28	36	43	51		

Performance Notes:

- Tested in accordance with ASHRAE Standard 70 – 2006 Method of Testing for Rating the Performance of Air Outlets and Inlets.
- Airflow is in cubic feet per minute [cfm].
- NC, sound pressure levels, are based on a room absorption of 10 dB re 10⁻¹² Watts, and a single diffuser/grille.
- Blanks "-" indicate an NC level below 15.
- All pressures are in inches of water column [in. w.g.].
- Pressures not listed can be calculated using the following formula:

$$P_{total} = P_{static} + P_{velocity}$$
- Grille tested without damper. Corrections for grille with damper:
 - Multiply negative static pressure by 1.3
 - Add 6 to listed NC.
- The performance tables are based on grilles with F border. For ED border the following correction factors must be applied due to the reduced core area of this border:
- Does not include pressure drop through filter on FF, FH models
- Does not include effects of ceiling radiation damper (80-FR, 80FF-FR, 81-FR, 82-FR).

Listed Core Area	Multiply Total Pressure	Add NC
.15 - .30	2.4	+15
.34 - .90	1.9	+10
1.07 - 1.80	1.4	+5
2.08 - 6.25	1.2	+2

PERFORMANCE DATA

85 - 45° Core

Core Area (sq. ft.)	Nominal Size		Core Velocity (fpm) Velocity Pressure (in. w.g.) Neg. Static Pressure (in. w.g.)	NC20					NC30		
				100	200	300	400	500	600	700	
				0.001	0.002	0.006	0.010	0.016	0.022	0.031	
			0.01	0.034	0.068	0.112	0.166	0.228	0.298		
0.15	7x4 6x5	Flow Rate (cfm)		15	30	45	60	75	90	105	
		Sound (NC)		-	-	-	15	21	26	30	
0.18	8x4 7x5	Flow Rate (cfm)		18	36	54	72	90	108	126	
		Sound (NC)		-	-	-	16	22	27	31	
0.22	10x4 8x5	Flow Rate (cfm)		22	44	66	88	110	132	154	
		Sound (NC)		-	-	-	16	22	27	32	
0.26	12x4 10x5	Flow Rate (cfm)		26	52	78	104	130	156	182	
		Sound (NC)		-	-	-	17	23	28	32	
0.30	14x4	Flow Rate (cfm)		30	60	90	120	150	180	210	
		Sound (NC)		-	-	-	18	24	28	33	
0.34	16x4 12x5	Flow Rate (cfm)		34	68	102	136	170	204	238	
		Sound (NC)		-	-	-	18	24	29	33	
0.39	18x4 14x5	Flow Rate (cfm)		39	78	117	156	195	234	273	
		Sound (NC)		-	-	-	18	24	29	34	
0.46	20x4 16x5	Flow Rate (cfm)		46	92	138	184	230	276	322	
		Sound (NC)		-	-	-	19	25	30	34	
0.52	24x4 18x5	Flow Rate (cfm)		52	104	156	208	260	312	364	
		Sound (NC)		-	-	-	19	26	30	35	
0.60	28x4 20x5	Flow Rate (cfm)		60	120	180	240	300	360	420	
		Sound (NC)		-	-	-	20	26	31	35	
0.69	30x4 24x5	Flow Rate (cfm)		69	138	207	276	345	414	483	
		Sound (NC)		-	-	-	20	27	31	36	
0.81	36x4 28x5	Flow Rate (cfm)		81	162	243	324	405	486	567	
		Sound (NC)		-	-	-	21	27	32	36	
0.90	40x4 30x5	Flow Rate (cfm)		90	180	270	360	450	540	630	
		Sound (NC)		-	-	-	21	27	32	37	
1.07	48x4 36x5	Flow Rate (cfm)		107	214	321	428	535	642	749	
		Sound (NC)		-	-	-	22	28	33	37	
1.18	34x6 24x8	Flow Rate (cfm)		118	236	354	472	590	708	826	
		Sound (NC)		-	-	-	22	28	33	38	
1.34	60x4 48x5	Flow Rate (cfm)		134	268	402	536	670	804	938	
		Sound (NC)		-	-	15	23	29	34	38	
1.60	72x4 30x8	Flow Rate (cfm)		160	320	480	640	800	960	1120	
		Sound (NC)		-	-	16	23	30	34	39	
1.80	60x5 48x6	Flow Rate (cfm)		180	360	540	720	900	1080	1260	
		Sound (NC)		-	-	16	24	30	35	39	
2.08	72x5 60x6	Flow Rate (cfm)		208	416	624	832	1040	1248	1456	
		Sound (NC)		-	-	17	24	30	35	40	
2.45	72x6 48x8	Flow Rate (cfm)		245	490	735	980	1225	1470	1715	
		Sound (NC)		-	-	17	25	31	36	40	
2.78	36x12 30x14	Flow Rate (cfm)		278	556	834	1112	1390	1668	1946	
		Sound (NC)		-	-	18	25	32	36	41	
3.11	60x8 48x10	Flow Rate (cfm)		311	622	933	1244	1555	1866	2177	
		Sound (NC)		-	-	18	26	32	37	41	
3.61	72x8 60x10	Flow Rate (cfm)		361	722	1083	1444	1805	2166	2527	
		Sound (NC)		-	-	19	26	32	37	42	
4.29	48x14 36x18	Flow Rate (cfm)		429	858	1287	1716	2145	2574	3003	
		Sound (NC)		-	-	19	27	33	38	42	
4.65	72x10 48x16	Flow Rate (cfm)		465	930	1395	1860	2325	2790	3255	
		Sound (NC)		-	-	20	27	33	38	42	
5.58	72x12 60x14	Flow Rate (cfm)		558	1116	1674	2232	2790	3348	3906	
		Sound (NC)		-	-	20	28	34	39	43	
6.25	72x14 60x16	Flow Rate (cfm)		625	1250	1875	2500	3125	3750	4375	
		Sound (NC)		-	-	21	28	34	39	44	

Performance Notes

1. Tested in accordance with ASHRAE Standard 70 – 2006 Method of Testing for Rating the Performance of Air Outlets and Inlets.
2. Airflow is in cubic feet per minute [cfm].
3. NC, sound pressure levels, are based on a room absorption of 10 dB re 10⁻¹² Watts, and a single diffuser/grille.
4. Blanks "-" indicate an NC level below 15.
5. All pressures are in inches of water column [in. w.g.].
6. Pressures not listed can be calculated using the following formula:

$$P_{total} = P_{static} + P_{velocity}$$