



RL/RM/RH

RECTANGULAR SILENCER



RL/RM/RH Rectangular Silencer

Rectangular silencers are designed to reduce noise in rectangular ductwork while minimizing system pressure drop. The simple design, relatively low cost, and high level of performance flexibility make rectangular silencers a reliable and cost-effective choice. A wide range of design and performance options allow rectangular silencers to be easily integrated into any HVAC system.




OPTIMIZED PERFORMANCE

Rectangular silencers are available with multiple internal geometries, providing the highest level of performance flexibility in the industry. Geometry variety allows rectangular silencers to match the requirements of any job to meet insertion loss requirements while minimizing pressure drop.

Maximum Insertion Loss

Geometry: L


Best suited for applications with very high insertion loss requirements. This configuration features a constant gap and smooth aerodynamic surface throughout.



Balanced Performance

Geometry: M


Providing an optimal balance between high insertion loss and low pressure drop, this configuration features a sloped tail arrangement allowing for static regain for improved pressure drop.



Ultra-Low Pressure Drop

Geometry: H

Best suited for applications where high air velocities cannot be avoided, this configuration minimizes the pressure drop that can occur at higher velocities.



TYPICAL APPLICATIONS


Rectangular silencers are intended for silencing noise in rectangular ductwork and a wide range of design options allow them to be integrated into any HVAC system with ease.

CONSTRUCTION


- + Geometry
 - Maximum insertion loss (L)
 - Balanced performance (M)
 - Ultra-low pressure drop (H)
- + Construction Type
 - 22 gauge
 - 18 gauge
 - 16 gauge
 - 10 gauge
- + Material
 - Galvanized Steel
 - Aluminum
 - 304 Stainless Steel
 - 316 Stainless Steel
 - Galvanneal
- + Optional Features
 - Extended casing
 - Media protection
 - Fiberglass cloth
 - Flanges
 - Transitions

EXTENDED CASINGS

- + The extended casing configuration is designed to control duct noise where high insertion loss is required at lower frequencies.
- + The extended outer shell holds additional acoustic media without changing the internal geometry used in standard rectangular silencers.



Extended casing provides additional insertion loss without contributing to system pressure drop




FILM LINERS

- + Commonly used in health care & education applications, film lined silencers are designed with a thin polymer film liner separating acoustic media from the air stream.
- + Film lined silencers use the same internal geometry as standard rectangular silencers. An acoustic standoff between the film liner and perforated metal ensures uncompromising acoustic performance.

Polymer film liner prevents acoustic media from entering the air stream

Acoustic standoff separates the polymer film and perforated metal to ensure acoustic performance is maintained



Silencer bank

Multi-module silencer

CUSTOMIZABLE

- + Available in a large range of sizes, rectangular silencers offer excellent flexibility to accommodate a variety of ductwork designs. For non-standard sizes, rectangular silencers can be custom built to suit the ductwork and application.
- + Silencers exceeding a width or height of 1200 mm are built in multiple components, then field assembled into banks that matching the duct dimensions.
- + Multiple module configurations are available to optimize silencer performance.


FIRE RATED

- + Class 1 index: flame/smoke < 25/50
- + ASTM E84, UL 723, NFPA 255



DIMENSIONAL DATA

Rectangular silencers are built to match the duct dimensions; therefore the width, height and length dimensions for the silencer must always be specified. Please consult the Standard Dimension Limits chart for available sizes.



* Bank width & height typically equal the duct dimensions.


Standard Dimension Limits

Bank Width		Bank Height		Length		Component Width		Component Height	
Min	Max	Min	Max	Min	Max	Min	Max	Min	Max
150	12000	150	12000	600	3000	150	1200	150	1200

1. All dimensions are in millimeters.
2. For sizes outside the standard range, please contact your local Holyoake office.
3. When overall width and/or height dimensions exceed the maximum component dimensions, the silencer will consist of multiple components.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600

Pressure Attenuation (PA) Code: B

Modules: 2

Geometry: L

Options: None

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB) / Generated Noise (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+3.8	15	3	5	11	22	28	21	18	15
	+2.5	8	3	5	11	22	28	21	18	15
	0	0	3	5	11	22	28	21	17	14
	-2.5	8	4	6	12	23	29	21	17	14
	-3.8	15	4	6	12	23	29	21	17	14
1500	+3.8	18	4	8	17	33	42	36	23	19
	+2.5	8	4	8	17	33	43	36	23	19
	0	0	4	8	17	33	43	36	22	18
	-2.5	8	5	9	18	34	44	36	22	18
	-3.8	18	5	9	18	34	44	36	22	18
2100	+3.8	18	6	11	21	43	47	42	27	21
	+2.5	8	6	11	21	43	47	42	27	21
	0	0	6	11	22	43	48	42	27	21
	-2.5	8	7	12	23	44	49	42	27	21
	-3.8	18	7	12	23	44	49	42	27	21
2700	+3.8	20	8	14	25	52	51	48	32	24
	+2.5	10	8	14	26	53	52	48	32	24
	0	0	8	14	26	53	52	48	31	23
	-2.5	10	9	15	27	54	53	48	31	23
	-3.8	20	9	15	28	55	54	48	31	23

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+3.8	37	20	22	30	30	25	16	10
	+2.5	28	20	15	23	22	15	10	10
	0	25	20	15	15	10	10	10	10
	-2.5	25	20	24	31	27	22	10	10
	-3.8	33	26	30	35	33	31	21	14

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600
Pressure Attenuation (PA) Code: F
Modules: 2
Geometry: L
Options: None

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+3.8	95	6	11	20	39	42	39	29	20
	+2.5	43	6	12	21	39	42	39	29	20
	0	0	7	12	22	40	43	39	28	19
	-2.5	43	7	13	23	42	45	39	28	19
	-3.8	95	7	14	24	42	45	39	28	19
1500	+3.8	105	8	17	31	50	53	55	47	32
	+2.5	48	8	17	32	51	54	55	47	31
	0	0	8	18	33	52	55	55	46	30
	-2.5	48	9	20	35	54	55	55	46	30
	-3.8	105	9	20	36	55	55	55	46	29
2100	+3.8	110	12	22	35	53	53	55	52	37
	+2.5	50	12	22	36	54	54	55	51	37
	0	0	13	23	38	55	55	55	51	36
	-2.5	50	13	25	40	55	55	55	51	35
	-3.8	110	14	26	41	55	55	55	50	35
2700	+3.8	125	15	26	39	53	53	55	55	43
	+2.5	55	16	27	40	54	54	55	55	42
	0	0	17	28	42	55	55	55	55	42
	-2.5	55	18	30	45	55	55	55	55	41
	-3.8	125	18	31	46	55	55	55	55	40

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+3.8	54	38	39	43	43	43	39	32
	+2.5	44	24	29	35	35	33	25	18
	0	25	20	15	15	10	10	10	10
	-2.5	39	31	34	38	37	37	30	23
	-3.8	47	39	41	43	43	45	42	35

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600

Pressure Attenuation (PA) Code: B

Modules: 1

Geometry: L

Options: None

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+3.8	15	4	6	11	19	14	11	10	9
	+2.5	5	4	6	11	19	14	11	10	9
	0	0	4	6	12	19	14	11	9	9
	-2.5	5	5	7	12	20	15	11	9	9
	-3.8	15	5	7	12	20	15	11	9	9
1500	+3.8	15	6	9	17	28	23	16	12	10
	+2.5	8	6	9	17	28	24	16	12	10
	0	0	6	9	17	28	24	16	12	10
	-2.5	8	6	10	18	29	24	16	12	10
	-3.8	15	6	10	18	29	25	16	12	10
2100	+3.8	15	8	12	22	37	33	21	14	11
	+2.5	8	8	12	23	37	33	21	14	11
	0	0	8	12	23	37	33	21	14	11
	-2.5	8	8	13	24	38	34	21	14	11
	-3.8	15	8	13	24	38	34	21	14	11
2700	+3.8	15	9	15	28	45	37	24	17	13
	+2.5	8	9	15	28	46	37	24	17	13
	0	0	9	15	29	46	37	24	16	12
	-2.5	8	10	16	30	47	38	24	16	12
	-3.8	15	10	16	30	48	38	24	16	12

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+3.8	37	20	22	30	30	25	16	10
	+2.5	28	20	15	23	22	15	10	10
	0	25	20	15	15	10	10	10	10
	-2.5	25	20	24	31	27	22	10	10
	-3.8	33	26	30	35	33	31	21	14

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600
Pressure Attenuation (PA) Code: F
Modules: 1
Geometry: L
Options: None

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+3.8	80	6	11	19	29	28	22	19	14
	+2.5	35	6	11	20	30	28	22	19	14
	0	0	6	11	21	30	29	22	18	13
	-2.5	35	7	12	22	31	30	22	18	13
	-3.8	80	7	12	23	32	30	22	18	13
1500	+3.8	88	9	17	28	44	44	38	23	16
	+2.5	38	10	17	29	45	44	38	22	16
	0	0	10	18	30	46	45	38	22	15
	-2.5	38	11	20	32	48	47	38	22	15
	-3.8	88	11	20	33	49	47	38	22	14
2100	+3.8	95	13	22	37	49	48	46	27	19
	+2.5	43	14	23	38	50	49	46	27	18
	0	0	15	24	40	51	50	46	26	18
	-2.5	43	16	26	43	53	52	46	26	17
	-3.8	95	16	27	44	54	53	46	26	17
2700	+3.8	100	17	28	46	53	53	53	31	21
	+2.5	45	18	29	47	54	54	53	31	21
	0	0	19	30	50	55	55	53	30	20
	-2.5	45	20	32	53	55	55	53	30	20
	-3.8	100	21	33	55	55	55	53	30	20

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+3.8	54	38	39	43	43	43	39	32
	+2.5	44	24	29	35	35	33	25	18
	0	25	20	15	15	10	10	10	10
	-2.5	39	31	34	38	37	37	30	23
	-3.8	47	39	41	43	43	45	42	35

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600

Pressure Attenuation (PA) Code: B

Modules: 2

Geometry: M

Options: None

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+6.4	25	2	4	9	21	26	20	15	14
	+3.8	10	2	4	9	21	26	20	15	14
	0	0	2	4	9	21	27	20	15	14
	-3.8	10	3	5	10	22	27	20	15	14
	-6.4	25	3	5	10	22	27	20	15	14
1500	+6.4	28	4	6	13	30	33	29	20	17
	+3.8	10	4	7	14	31	34	29	20	17
	0	0	4	7	14	31	35	29	20	16
	-3.8	10	4	7	15	32	35	29	20	16
	-6.4	28	4	7	15	33	36	29	20	16
2100	+6.4	28	5	9	18	40	41	38	25	19
	+3.8	10	6	9	18	41	42	38	25	19
	0	0	6	9	19	41	43	38	25	19
	-3.8	10	6	10	20	42	43	38	25	19
	-6.4	28	6	10	20	43	44	38	24	18
2700	+6.4	35	7	11	22	50	49	47	30	22
	+3.8	13	7	11	22	50	49	47	29	22
	0	0	7	11	23	51	51	47	29	21
	-3.8	13	8	12	25	53	52	47	29	21
	-6.4	35	8	12	25	53	52	47	29	21

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+6.4	45	31	23	34	35	31	26	22
	+3.8	31	20	15	21	26	18	10	10
	0	25	20	15	15	10	10	10	10
	-3.8	25	20	15	23	30	23	18	10
	-6.4	48	25	29	40	44	46	46	38

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600
Pressure Attenuation (PA) Code: F
Modules: 2
Geometry: M
Options: None

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+6.4	165	4	7	14	28	35	38	26	20
	+3.8	60	4	8	15	29	36	38	26	19
	0	0	4	8	16	30	38	38	26	19
	-3.8	60	5	9	18	32	40	38	26	18
	-6.4	165	5	10	19	33	41	38	25	18
1500	+6.4	162	7	12	20	42	49	50	35	24
	+3.8	58	8	12	22	44	50	50	35	24
	0	0	9	13	23	45	52	50	34	22
	-3.8	58	9	15	26	47	55	50	34	21
	-6.4	162	10	15	27	49	55	50	34	21
2100	+6.4	162	11	17	25	47	50	53	45	31
	+3.8	58	12	18	27	48	52	53	45	30
	0	0	13	20	29	50	54	53	44	28
	-3.8	58	14	22	32	53	55	53	43	27
	-6.4	162	15	23	34	54	55	53	43	26
2700	+6.4	212	15	23	31	51	51	55	55	37
	+3.8	78	16	24	32	53	53	55	54	36
	0	0	17	26	35	55	55	55	53	34
	-3.8	78	18	29	39	55	55	55	53	33
	-6.4	212	19	30	41	55	55	55	52	31

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+6.4	65	55	51	51	48	49	50	46
	+3.8	50	38	30	38	38	36	32	28
	0	25	20	15	15	10	10	10	10
	-3.8	44	21	24	37	41	41	41	32
	-6.4	59	36	39	47	50	55	58	51

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600

Pressure Attenuation (PA) Code: B

Modules: 1

Geometry: M

Options: None

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+6.4	25	3	5	9	18	14	11	9	7
	+3.8	10	3	5	9	18	14	11	9	7
	0	0	3	5	10	18	14	11	9	7
	-3.8	10	4	6	10	19	15	11	9	7
	-6.4	25	4	6	10	19	15	11	9	7
1500	+6.4	25	5	7	14	27	22	15	11	9
	+3.8	10	5	8	14	27	23	15	11	9
	0	0	5	8	15	27	23	15	11	9
	-3.8	10	5	8	16	28	23	15	11	9
	-6.4	25	5	9	16	28	24	15	11	9
2100	+6.4	25	6	10	19	35	30	19	13	11
	+3.8	10	6	10	20	36	31	19	13	11
	0	0	6	10	20	36	31	19	12	10
	-3.8	10	7	11	21	37	32	19	12	10
	-6.4	25	7	11	22	38	33	19	12	10
2700	+6.4	30	8	13	23	45	33	23	16	13
	+3.8	10	8	13	24	45	34	23	16	13
	0	0	8	13	25	46	35	23	15	12
	-3.8	10	9	14	26	48	35	23	15	12
	-6.4	30	9	14	27	48	36	23	15	12

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+6.4	45	31	23	34	35	31	26	22
	+3.8	31	20	15	21	26	18	10	10
	0	25	20	15	15	10	10	10	10
	-3.8	25	20	15	23	30	23	18	10
	-6.4	38	20	19	33	38	37	35	26

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600
Pressure Attenuation (PA) Code: F
Modules: 1
Geometry: M
Options: None

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+6.4	127	5	9	15	28	24	21	17	13
	+3.8	45	5	9	16	29	25	21	17	12
	0	0	5	10	18	30	26	21	16	12
	-3.8	45	6	11	19	32	27	21	16	12
	-6.4	127	6	11	20	33	28	21	16	11
1500	+6.4	165	7	14	25	43	41	34	21	16
	+3.8	60	8	15	26	44	43	34	20	15
	0	0	8	16	28	46	45	34	20	15
	-3.8	60	9	18	31	49	47	34	20	14
	-6.4	165	10	19	33	50	48	34	20	14
2100	+6.4	165	11	19	32	47	46	43	25	18
	+3.8	60	11	21	34	49	48	43	25	17
	0	0	12	23	37	51	50	43	25	17
	-3.8	60	14	25	40	53	52	43	24	16
	-6.4	165	14	26	42	55	54	43	24	15
2700	+6.4	197	15	25	39	51	51	52	30	20
	+3.8	70	16	26	41	53	53	52	29	19
	0	0	17	29	45	55	55	52	29	18
	-3.8	70	19	31	49	55	55	52	28	17
	-6.4	197	20	33	52	55	55	52	28	16

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+6.4	65	55	51	51	48	49	50	46
	+3.8	50	38	30	38	38	36	32	28
	0	25	20	15	15	10	10	10	10
	-3.8	44	21	24	37	41	41	41	32
	-6.4	59	36	39	47	50	55	58	51

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600

Pressure Attenuation (PA) Code: B

Modules: 2

Geometry: H

Options: None

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+10.2	43	2	3	8	17	22	20	14	12
	+5.1	10	3	3	8	17	22	20	14	12
	0	0	3	3	8	17	23	20	14	12
	-5.1	10	3	4	9	18	23	20	14	12
	-10.2	43	3	4	9	18	24	20	14	11
1500	+10.2	45	4	5	11	24	31	25	16	13
	+5.1	13	4	5	11	24	32	25	16	13
	0	0	4	5	11	25	32	25	16	13
	-5.1	13	4	6	12	25	33	25	16	12
	-10.2	45	5	6	12	26	33	25	16	12
2100	+10.2	50	6	7	13	31	40	30	19	14
	+5.1	13	6	7	14	32	41	30	19	14
	0	0	6	7	14	32	42	30	19	14
	-5.1	13	6	8	15	33	42	30	19	13
	-10.2	50	6	8	16	33	43	30	18	13
2700	+10.2	55	7	9	16	38	49	35	21	15
	+5.1	13	7	9	17	39	50	35	21	15
	0	0	8	9	17	39	51	35	21	14
	-5.1	13	8	10	18	40	52	35	21	14
	-10.2	55	8	10	19	41	53	35	21	14

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	10.2	50	36	32	31	38	38	38	34
	5.1	30	20	15	15	25	21	17	14
	0	25	20	15	15	10	10	10	10
	-5.1	34	20	15	15	27	31	29	25
	-10.2	51	37	33	36	43	47	48	44

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600
Pressure Attenuation (PA) Code: F
Modules: 2
Geometry: H
Options: None

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+10.2	170	4	7	12	26	30	29	22	17
	+5.1	43	4	7	13	27	31	29	22	17
	0	0	4	7	13	27	31	29	22	16
	-5.1	43	5	8	14	28	32	29	22	16
	-10.2	170	5	8	15	29	33	29	22	16
1500	+10.2	172	6	10	19	37	45	40	31	21
	+5.1	43	6	10	20	38	46	40	31	20
	0	0	6	10	20	38	47	40	30	20
	-5.1	43	7	11	21	39	49	40	30	20
	-10.2	172	7	11	22	40	50	40	30	19
2100	+10.2	205	7	12	24	47	49	48	36	25
	+5.1	50	8	12	25	48	50	48	36	24
	0	0	8	13	26	49	51	48	35	24
	-5.1	50	8	14	27	51	53	48	35	23
	-10.2	205	9	14	28	52	54	48	35	23
2700	+10.2	222	9	14	29	53	53	55	41	29
	+5.1	55	9	15	30	54	54	55	41	28
	0	0	10	15	31	55	55	55	40	27
	-5.1	55	10	16	33	55	55	55	40	27
	-10.2	222	11	17	34	55	55	55	40	26

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+10.2	69	58	56	52	50	55	58	54
	+5.1	50	36	32	31	38	38	38	34
	0	25	20	15	15	10	10	10	10
	-5.1	51	37	33	36	43	47	48	44
	-10.2	69	58	58	58	59	63	68	62

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600

Pressure Attenuation (PA) Code: B

Modules: 1

Geometry: H

Options: None

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+10.2	40	2	4	8	15	12	9	8	6
	+5.1	10	2	4	8	15	12	9	8	6
	0	0	2	4	8	15	12	9	7	5
	-5.1	10	3	5	9	16	13	9	7	5
	-10.2	40	3	5	9	16	13	9	7	5
1500	+10.2	43	4	6	11	22	17	12	9	7
	+5.1	10	4	6	12	22	17	12	9	7
	0	0	4	6	12	23	17	12	9	7
	-5.1	10	4	7	13	23	18	12	9	6
	-10.2	43	4	7	13	24	18	12	9	6
2100	+10.2	43	5	8	15	29	21	15	10	8
	+5.1	10	6	8	16	30	22	15	10	8
	0	0	6	8	16	30	22	15	10	8
	-5.1	10	6	9	17	31	23	15	10	8
	-10.2	43	6	9	18	31	23	15	10	7
2700	+10.2	45	7	10	19	36	26	17	12	9
	+5.1	10	7	10	20	37	27	17	12	9
	0	0	7	10	20	37	27	17	12	9
	-5.1	10	8	11	21	38	28	17	12	9
	-10.2	45	8	11	22	39	28	17	12	8

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+10.2	50	36	32	31	38	38	38	34
	+5.1	30	20	15	15	25	21	17	14
	0	25	20	15	15	10	10	10	10
	-5.1	34	20	15	15	27	31	29	25
	-10.2	51	37	33	36	43	47	48	44

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600
Pressure Attenuation (PA) Code: F
Modules: 1
Geometry: H
Options: None

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+10.2	200	4	7	15	23	21	17	15	13
	+5.1	50	5	8	15	24	22	17	15	13
	0	0	5	8	16	24	22	17	15	13
	-5.1	50	5	8	17	25	23	17	15	13
	-10.2	200	5	9	17	26	24	17	15	12
1500	+10.2	197	6	12	22	33	33	25	18	14
	+5.1	50	6	12	23	34	34	25	18	14
	0	0	7	13	24	35	34	25	18	14
	-5.1	50	7	13	25	36	35	25	18	13
	-10.2	197	7	14	26	36	36	25	18	13
2100	+10.2	197	8	16	29	43	42	33	21	15
	+5.1	50	8	17	30	44	43	33	21	15
	0	0	9	18	32	45	44	33	20	14
	-5.1	50	9	19	33	46	46	33	20	14
	-10.2	197	9	19	34	47	47	33	20	14
2700	+10.2	192	10	21	36	53	53	41	23	16
	+5.1	48	10	22	38	54	54	41	23	16
	0	0	10	23	39	55	55	41	23	15
	-5.1	48	11	24	41	55	55	41	23	15
	-10.2	192	11	25	43	55	55	41	23	14

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+10.2	69	58	56	52	50	55	58	54
	+5.1	50	36	32	31	38	38	38	34
	0	25	20	15	15	10	10	10	10
	-5.1	51	37	33	36	43	47	48	44
	-10.2	69	58	58	58	59	63	68	62

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (in.): 24

Pressure Attenuation (PA) Code: B

Modules: 2

Geometry: L

Options: Film lined

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+3.8	15	4	5	8	16	24	24	18	13
	+2.5	8	4	5	9	16	24	24	18	12
	0	0	4	5	9	16	24	24	17	12
	-2.5	8	4	5	9	16	25	24	17	12
	-3.8	15	4	5	9	16	25	24	17	12
1500	+3.8	18	5	7	13	23	36	39	23	16
	+2.5	8	5	7	13	23	36	39	23	16
	0	0	5	8	13	24	37	39	22	16
	-2.5	8	5	8	14	24	37	39	22	16
	-3.8	18	5	8	14	24	38	39	22	16
2100	+3.8	18	7	10	16	30	40	46	27	18
	+2.5	8	7	10	16	30	40	46	27	18
	0	0	7	10	17	31	41	46	27	18
	-2.5	8	7	11	17	31	41	46	27	18
	-3.8	18	7	11	17	31	42	46	27	18
2700	+3.8	20	9	13	19	37	44	53	32	20
	+2.5	10	9	13	19	37	44	53	32	20
	0	0	9	13	20	38	45	53	31	20
	-2.5	10	10	13	21	38	45	53	31	20
	-3.8	20	10	14	21	38	46	53	31	20

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+3.8	37	20	22	30	30	25	16	10
	+2.5	28	20	15	23	22	15	10	10
	0	25	20	15	15	10	10	10	10
	-2.5	25	20	24	31	27	22	10	10
	-3.8	33	26	30	35	33	31	21	14

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600
Pressure Attenuation (PA) Code: F
Modules: 2
Geometry: L
Options: Film lined

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+3.8	95	7	10	15	27	35	42	29	17
	+2.5	43	7	11	16	28	36	42	29	17
	0	0	7	11	16	28	37	42	28	17
	-2.5	43	8	12	17	29	38	42	28	16
	-3.8	95	8	12	18	30	39	42	28	16
1500	+3.8	105	9	15	23	35	45	55	47	27
	+2.5	48	9	16	24	36	46	55	47	27
	0	0	9	17	25	37	47	55	46	26
	-2.5	48	10	18	27	38	49	55	46	25
	-3.8	105	10	18	27	39	49	55	46	25
2100	+3.8	110	13	19	26	37	45	55	52	32
	+2.5	50	13	20	27	38	46	55	51	31
	0	0	14	21	29	39	47	55	51	31
	-2.5	50	15	22	30	40	49	55	51	30
	-3.8	110	15	23	31	41	49	55	50	30
2700	+3.8	125	17	24	29	37	45	55	55	36
	+2.5	55	17	24	30	38	46	55	55	36
	0	0	19	26	32	39	47	55	55	35
	-2.5	55	20	27	34	40	49	55	55	35
	-3.8	125	20	28	35	41	49	55	55	34

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+3.8	54	38	39	43	43	43	39	32
	+2.5	44	24	29	35	35	33	25	18
	0	25	20	15	15	10	10	10	10
	-2.5	39	31	34	38	37	37	30	23
	-3.8	47	39	41	43	43	45	42	35

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600

Pressure Attenuation (PA) Code: B

Modules: 1

Geometry: L

Options: Film lined

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+3.8	15	5	6	8	14	12	13	10	8
	+2.5	5	5	6	9	14	12	13	10	8
	0	0	5	6	9	14	12	13	9	8
	-2.5	5	5	6	9	14	13	13	9	8
	-3.8	15	5	6	9	14	13	13	9	8
1500	+3.8	15	6	8	13	20	20	18	12	9
	+2.5	8	7	8	13	20	20	18	12	9
	0	0	7	9	13	20	20	18	12	9
	-2.5	8	7	9	14	20	21	18	12	9
	-3.8	15	7	9	14	21	21	18	12	9
2100	+3.8	15	8	11	17	26	28	24	14	10
	+2.5	8	8	11	17	26	28	24	14	10
	0	0	9	11	18	26	29	24	14	10
	-2.5	8	9	12	18	27	29	24	14	10
	-3.8	15	9	12	18	27	29	24	14	10
2700	+3.8	15	10	13	21	32	31	27	17	11
	+2.5	8	10	14	21	32	31	27	17	11
	0	0	10	14	22	33	32	27	16	11
	-2.5	8	11	14	23	33	32	27	16	11
	-3.8	15	11	15	23	33	33	27	16	11

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+3.8	37	20	22	30	30	25	16	10
	+2.5	28	20	15	23	22	15	10	10
	0	25	20	15	15	10	10	10	10
	-2.5	25	20	24	31	27	22	10	10
	-3.8	33	26	30	35	33	31	21	14

Generated Noise Corrections


Silencer Face Area (Sqrm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600

Pressure Attenuation (PA) Code: F

Modules: 1

Geometry: L

Options: Film Lined

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+3.8	80	6	10	14	21	24	25	19	12
	+2.5	35	7	10	15	21	24	25	19	12
	0	0	7	10	16	21	25	25	18	12
	-2.5	35	7	11	17	22	25	25	18	11
	-3.8	80	8	11	17	22	26	25	18	11
1500	+3.8	88	10	15	21	31	37	42	23	13
	+2.5	38	11	16	22	32	38	42	22	13
	0	0	11	17	23	33	39	42	22	13
	-2.5	38	12	18	24	34	40	42	22	13
	-3.8	88	12	18	25	34	40	42	22	12
2100	+3.8	95	15	20	28	35	41	50	27	16
	+2.5	43	15	21	29	35	42	50	27	16
	0	0	16	22	30	36	43	50	26	15
	-2.5	43	17	23	32	37	44	50	26	15
	-3.8	95	18	24	33	38	45	50	26	15
2700	+3.8	100	19	25	35	37	45	55	31	18
	+2.5	45	20	26	36	38	46	55	31	18
	0	0	21	27	38	39	47	55	30	17
	-2.5	45	22	29	40	40	49	55	30	17
	-3.8	100	23	30	41	41	49	55	30	17

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+3.8	54	38	39	43	43	43	39	32
	+2.5	44	24	29	35	35	33	25	18
	0	25	20	15	15	10	10	10	10
	-2.5	39	31	34	38	37	37	30	23
	-3.8	47	39	41	43	43	45	42	35

Generated Noise Corrections


Silencer Face Area (Sqrm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600

Pressure Attenuation (PA) Code: B

Modules: 2

Geometry: M

Options: Film Lined

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+6.4	25	3	4	7	15	22	22	15	12
	+3.8	10	3	4	7	15	22	22	15	12
	0	0	3	4	7	15	23	22	15	12
	-3.8	10	3	4	8	16	23	22	15	12
	-6.4	25	3	4	8	16	23	22	15	12
1500	+6.4	28	4	6	10	21	28	32	20	14
	+3.8	10	4	6	10	22	29	32	20	14
	0	0	5	6	11	22	29	32	20	14
	-3.8	10	5	6	11	23	30	32	20	14
	-6.4	28	5	7	12	23	30	32	20	14
2100	+6.4	28	6	8	13	28	35	42	25	16
	+3.8	10	6	8	14	29	35	42	25	16
	0	0	6	8	14	29	36	42	25	16
	-3.8	10	7	9	15	30	37	42	25	16
	-6.4	28	7	9	15	30	38	42	24	16
2700	+6.4	35	8	10	17	35	41	51	30	19
	+3.8	13	8	10	17	35	42	51	29	18
	0	0	8	10	18	36	43	51	29	18
	-3.8	13	9	11	19	37	44	51	29	18
	-6.4	35	9	11	19	38	45	51	29	18

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+6.4	45	31	23	34	35	31	26	22
	+3.8	31	20	15	21	26	18	10	10
	0	25	20	15	15	10	10	10	10
	-3.8	25	20	15	23	30	23	18	10
	-6.4	38	20	19	33	38	37	35	26

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600

Pressure Attenuation (PA) Code: F

Modules: 2

Geometry: M

Options: Film Lined

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+6.4	165	4	7	11	20	30	41	26	17
	+3.8	60	5	7	11	21	31	41	26	16
	0	0	5	8	12	21	32	41	26	16
	-3.8	60	5	8	13	22	34	41	26	15
	-6.4	165	6	9	14	23	35	41	25	15
1500	+6.4	162	8	11	15	30	41	55	35	21
	+3.8	58	9	11	16	31	43	55	35	20
	0	0	9	12	18	32	45	55	34	19
	-3.8	58	10	13	19	33	47	55	34	18
	-6.4	162	11	14	20	34	48	55	34	18
2100	+6.4	162	12	16	19	33	43	55	45	26
	+3.8	58	13	17	20	34	44	55	45	25
	0	0	14	18	22	35	46	55	44	24
	-3.8	58	15	20	24	37	48	55	43	23
	-6.4	162	16	21	26	38	49	55	43	22
2700	+6.4	212	16	21	23	36	44	55	55	32
	+3.8	78	17	22	24	37	45	55	54	31
	0	0	19	24	27	39	47	55	53	29
	-3.8	78	20	26	29	41	49	55	53	28
	-6.4	212	21	27	31	42	51	55	52	27

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+6.4	65	55	51	51	48	49	50	46
	+3.8	50	38	30	38	38	36	32	28
	0	25	20	15	15	10	10	10	10
	-3.8	44	21	24	37	41	41	41	32
	-6.4	59	36	39	47	50	55	58	51

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600

Pressure Attenuation (PA) Code: B

Modules: 1

Geometry: M

Options: Film Lined

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+6.4	25	4	5	7	13	12	13	9	6
	+3.8	10	4	5	7	13	12	13	9	6
	0	0	4	5	7	13	12	13	9	6
	-3.8	10	4	5	8	13	13	13	9	6
	-6.4	25	4	5	8	14	13	13	9	6
1500	+6.4	25	5	7	11	19	19	17	11	8
	+3.8	10	5	7	11	19	19	17	11	8
	0	0	5	7	11	19	20	17	11	8
	-3.8	10	6	8	12	20	20	17	11	7
	-6.4	25	6	8	12	20	20	17	11	7
2100	+6.4	25	7	9	14	25	26	21	13	9
	+3.8	10	7	9	15	25	26	21	13	9
	0	0	7	9	15	26	27	21	12	9
	-3.8	10	7	10	16	26	27	21	12	9
	-6.4	25	8	10	17	27	28	21	12	9
2700	+6.4	30	9	11	17	32	28	26	16	11
	+3.8	10	9	12	18	32	29	26	16	11
	0	0	9	12	19	33	30	26	15	11
	-3.8	10	10	13	20	33	30	26	15	11
	-6.4	30	10	13	20	34	31	26	15	11

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+6.4	45	31	23	34	35	31	26	22
	+3.8	31	20	15	21	26	18	10	10
	0	25	20	15	15	10	10	10	10
	-3.8	25	20	15	23	30	23	18	10
	-6.4	38	20	19	33	38	37	35	26

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (in.): 24
Pressure Attenuation (PA) Code: F
Modules: 1
Geometry: M
Options: Film Lined

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+6.4	127	5	8	12	20	21	23	17	11
	+3.8	45	5	8	12	21	21	23	17	11
	0	0	6	9	13	21	22	23	16	10
	-3.8	45	6	10	15	22	23	23	16	10
	-6.4	127	7	10	15	23	24	23	16	10
1500	+6.4	165	8	13	19	30	35	37	21	13
	+3.8	60	9	14	20	31	36	37	20	13
	0	0	9	15	21	33	38	37	20	13
	-3.8	60	10	16	23	34	40	37	20	12
	-6.4	165	11	17	25	35	41	37	20	12
2100	+6.4	165	12	18	24	33	39	47	25	15
	+3.8	60	13	19	25	34	41	47	25	15
	0	0	14	20	28	36	43	47	25	14
	-3.8	60	15	22	30	37	44	47	24	13
	-6.4	165	16	23	32	38	46	47	24	13
2700	+6.4	197	17	22	29	36	44	55	30	17
	+3.8	70	18	24	31	37	45	55	29	16
	0	0	19	26	34	39	47	55	29	15
	-3.8	70	21	28	37	41	49	55	28	15
	-6.4	197	22	30	39	42	51	55	28	14

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+6.4	65	55	51	51	48	49	50	46
	+3.8	50	38	30	38	38	36	32	28
	0	25	20	15	15	10	10	10	10
	-3.8	44	21	24	37	41	41	41	32
	-6.4	59	36	39	47	50	55	58	51

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600

Pressure Attenuation (PA) Code: B

Modules: 2

Geometry: H

Options: Film Lined

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+10.2	43	3	3	6	12	19	22	14	10
	+5.1	10	3	3	6	12	19	22	14	10
	0	0	3	3	6	12	20	22	14	10
	-5.1	10	3	3	7	13	20	22	14	10
	-10.2	43	3	3	7	13	20	22	14	10
1500	+10.2	45	4	5	8	17	26	28	16	11
	+5.1	13	5	5	8	17	27	28	16	11
	0	0	5	5	9	18	27	28	16	11
	-5.1	13	5	5	9	18	28	28	16	11
	-10.2	45	5	5	9	18	28	28	16	11
2100	+10.2	50	6	6	10	22	34	33	19	12
	+5.1	13	6	7	11	22	35	33	19	12
	0	0	7	7	11	23	35	33	19	12
	-5.1	13	7	7	11	23	36	33	19	11
	-10.2	50	7	7	12	24	37	33	18	11
2700	+10.2	55	8	8	12	27	42	39	21	13
	+5.1	13	8	8	13	27	42	39	21	13
	0	0	8	9	13	28	43	39	21	12
	-5.1	13	9	9	14	28	44	39	21	12
	-10.2	55	9	9	14	29	45	39	21	12

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+10.2	50	36	32	31	38	38	38	34
	+5.1	30	20	15	15	25	21	17	14
	0	25	20	15	15	10	10	10	10
	-5.1	34	20	15	15	27	31	29	25
	-10.2	51	37	33	36	43	47	48	44

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600
Pressure Attenuation (PA) Code: F
Modules: 2
Geometry: H
Options: Film Lined

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+10.2	170	5	6	9	19	26	32	22	14
	+5.1	43	5	7	10	19	26	32	22	14
	0	0	5	7	10	19	27	32	22	14
	-5.1	43	5	7	11	20	27	32	22	14
	-10.2	170	5	7	11	20	28	32	22	13
1500	+10.2	172	6	9	14	26	39	44	31	18
	+5.1	43	7	9	15	26	40	44	31	17
	0	0	7	9	15	27	40	44	30	17
	-5.1	43	7	10	16	28	41	44	30	17
	-10.2	172	7	10	17	28	42	44	30	16
2100	+10.2	205	8	11	18	33	42	53	36	21
	+5.1	50	8	11	19	34	43	53	36	21
	0	0	9	12	20	35	44	53	35	20
	-5.1	50	9	12	21	36	45	53	35	20
	-10.2	205	10	13	21	36	46	53	35	19
2700	+10.2	222	10	13	22	37	45	55	41	24
	+5.1	55	10	13	23	38	46	55	41	24
	0	0	11	14	24	39	47	55	40	23
	-5.1	55	11	15	25	40	48	55	40	23
	-10.2	222	12	15	26	41	49	55	40	22

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+10.2	69	58	56	52	50	55	58	54
	+5.1	50	36	32	31	38	38	38	34
	0	25	20	15	15	10	10	10	10
	-5.1	51	37	33	36	43	47	48	44
	-10.2	69	58	58	58	59	63	68	62

Generated Noise Corrections


Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600

Pressure Attenuation (PA) Code: B

Modules: 1

Geometry: H

Options: Film Lined

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+10.2	40	3	4	6	11	10	10	8	5
	+5.1	10	3	4	6	11	10	10	8	5
	0	0	3	4	6	11	11	10	7	5
	-5.1	10	3	4	7	11	11	10	7	5
	-10.2	40	3	4	7	11	11	10	7	5
1500	+10.2	43	4	5	9	16	14	13	9	6
	+5.1	10	4	6	9	16	15	13	9	6
	0	0	5	6	9	16	15	13	9	6
	-5.1	10	5	6	10	16	15	13	9	6
	-10.2	43	5	6	10	17	15	13	9	5
2100	+10.2	43	6	7	12	20	18	16	10	7
	+5.1	10	6	7	12	21	19	16	10	7
	0	0	6	8	12	21	19	16	10	7
	-5.1	10	7	8	13	22	19	16	10	6
	-10.2	43	7	8	13	22	20	16	10	6
2700	+10.2	45	8	9	14	25	22	19	12	8
	+5.1	10	8	9	15	26	23	19	12	8
	0	0	8	9	15	26	23	19	12	7
	-5.1	10	8	10	16	27	24	19	12	7
	-10.2	45	9	10	17	27	24	19	12	7

Generated Noise (GN)

Length (mm)	Face Velocity (m/s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+10.2	50	36	32	31	38	38	38	34
	+5.1	30	20	15	15	25	21	17	14
	0	25	20	15	15	10	10	10	10
	-5.1	34	20	15	15	27	31	29	25
	-10.2	51	37	33	36	43	47	48	44

Generated Noise Corrections


Silencer Face Area (Sqrm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.

RL/RM/RH

Rectangular Silencer



PERFORMANCE DATA

Width (mm): 600
Pressure Attenuation (PA) Code: F
Modules: 1
Geometry: H
Options: Film Lined

Dynamic Insertion Loss (DIL)

Length (mm)	Face Velocity (m/s)	Pressure Drop (Pa)	Dynamic Insertion Loss (dB)							
			63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
900	+10.2	200	5	7	11	17	18	19	15	11
	+5.1	50	5	7	12	17	19	19	15	11
	0	0	5	7	12	17	19	19	15	11
	-5.1	50	6	8	13	18	20	19	15	11
	-10.2	200	6	8	13	18	20	19	15	11
1500	+10.2	197	7	11	16	23	28	28	18	12
	+5.1	50	7	11	17	24	29	28	18	12
	0	0	7	12	18	25	29	28	18	12
	-5.1	50	8	12	19	25	30	28	18	11
	-10.2	197	8	13	20	26	31	28	18	11
2100	+10.2	197	9	15	22	30	36	36	21	13
	+5.1	50	9	15	23	31	37	36	21	13
	0	0	9	16	24	32	38	36	20	12
	-5.1	50	10	17	25	32	39	36	20	12
	-10.2	197	10	17	26	33	40	36	20	12
2700	+10.2	192	10	19	27	37	45	45	23	14
	+5.1	48	11	19	28	38	46	45	23	13
	0	0	11	20	30	39	47	45	23	13
	-5.1	48	12	21	31	40	48	45	23	13
	-10.2	192	12	22	32	41	49	45	23	12

Generated Noise (GN)

Length (mm)	Face Velocity (./s)	Generated Noise (dB)							
		63 Hz	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	8000 Hz
All Lengths	+10.2	69	58	56	52	50	55	58	54
	+5.1	50	36	32	31	38	38	38	34
	0	25	20	15	15	10	10	10	10
	-5.1	51	37	33	36	43	47	48	44
	-10.2	69	58	58	58	59	63	68	62

Generated Noise Corrections

Silencer Face Area (Sqm)	0.05	0.09	0.19	0.37	0.74	1.49	2.97	5.95	11.89
dB Addition or Reduction	-9	-6	-3	0	+3	+6	+9	+12	+15

Performance Notes:

1. Data tables are derived from test data in conformance with ASTM E477-20.
2. "+" indicates performance data for forward flow (supply) applications.
3. "-" indicates performance data for reverse flow (return) applications.
4. Dynamic Insertion Loss is limited to 55 dB due to flanking.
5. For performance data specific to a configuration not cataloged, please use Price AIO Selection Software.
6. The performance data above is based on a 0.6 x 0.6 meter component.



Product Improvement is a continuing endeavour at Price. Therefore, specifications are subject to change without notice. Consult your Price Sales Representative for current specifications or more detailed information. Not all products may be available in all geographic areas. All goods described in this document are warranted as described in the Limited Warranty shown at priceindustries.com. The complete Price product catalog can be viewed online at priceindustries.com.