



SLOT WIDTH S	W	NOM. INLET				
		6" (152mm)	8" (203mm)	10" (254mm)	12" (305mm)	14" (356mm)
1" (25mm)	3" (76mm)	•	•	◦	◦	
1 1/2" (38mm)	3 1/2" (89mm)	•	•	◦	◦	
2" (51mm)	4" (102mm)		•	◦	◦	
2 1/2" (64mm)	4 1/2" (114mm)			◦	◦	
3" (76mm)	5" (127mm)			◦	◦	◦

- SUPPLIED AS EQUIVALENT FLAT OVAL SIZE:
12" (305mm) = 8" x 14 3/32" (203mm x 358mm)

- 10" (254mm) = 8" x 10 15/16" (203mm x 278mm)
- 14" (356mm) = 8" x 17 1/4" (203mm x 438mm)

NOMINAL LENGTH:

- 24" (610mm)
- 36" (914mm)
- 48" (1219mm)
- 60" (1524mm)

MATERIAL:

- COATED STEEL

FINISH:

- MILL FINISH

INSULATION OPTIONS:

- CF – INTERNAL COATED FIBERGLASS
- FF – INTERNAL FIBER FREE FOAM

NOTES:

- ENDCAPS ARE UNINSULATED
- WHEN PLENUM ENDCAPS ARE NOT POSITIONED DIRECTLY OVER THE DIFFUSER SPACER BAR, INSTALL MB BLANKOFF FROM PLENUM ENDCAP TO NEXT SPACER BAR
- USE WITH CF TYPE 41
- SEE INSTALLATION INSTRUCTION I100036
- VCR8EC – OPTIONAL VCR8EC CABLE OPERATED DAMPER (NECK MOUNTED, ROUND INLETS ONLY)

ALL METRIC DIMENSIONS () ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

PROJECT:		PRICE®	
ENGINEER:		<i>MG</i>	CFP CUSTOM FLOW ENGINEERED PLENUMS TYPE 41
CUSTOMER:			
SUBMITTAL DATE:	SPEC. SYMBOL:	2022/04/19	