


# Security Camera

The Node Security Camera is a recessed-mount HDTV 1080p fixed mini dome camera.

The Security Camera has been designed to be visually consistent with the Node product range.



## Product Features

- HDTV 1080p/2MP video with WDR
- Easy to install
- 3-axis camera angle adjustment
- Available in various finishes

## Specifications

	Diameter	Height	Protrusion
<b>Recessed Channel</b>	90mm/3.54 in.	87mm/3.42 in.	26mm/1.02 in.
<b>Trimless Mount</b>	90mm/3.54 in.	87mm/3.42 in.	26mm/1.02 in.
<b>Flush Channel</b>	90mm/3.54 in.	87mm/3.42 in.	26mm/1.02 in.

### General

- Memory: 512MB RAM, 512 MB Flash
- Storage: microSD
- Operating Temperature: 0°C to 45°C
- Humidity: 15-85% RH

### Camera

- Image Sensor: Fixed Focus, Fixed Iris 1/3" Progressive Scan RGB CMOS
- Lens: 2.8mm, F2.0
- Resolution: 1920x1080 (1080p) to 320x240

### Input

- Power: Power over Ethernet (PoE) Type 1 Class 1, Typical 2.8W

### Connection Type

- Shielded RJ45

### Field of View

- Horizontal: 106°
- Vertical: 59°

### Camera Angle Adjustment

- Pan: ±105°
- Tilt: ±85°
- Rotate: ±175°

### Communication Protocols

- Supported Protocols: IPv4, IPv6 USGv6, HTTP, HTTPSa, SSL/TLSa, QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, Bonjour, UPnP, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, LLDP