


DBH - Drop Box with HCD Drum Diffusers



Capacity	W	Н	D	Α	В	CFM Range
7.5T	31 1/4"	8 1/2"	18 7/8"	18"	6"	600 - 3,000
	(794mm)	(216mm)	(479mm)	(457mm)	(152mm)	
15T	40 1/4"	12 1/4"	25 7/8"	25"	10"	4,000-6,000
	(1022mm)	(311mm)	(657mm)	(635mm)	(254mm)	4,000-0,000
30T	56 1/4"	17 1/4"	40 7/8"	40"	15"	8,000-12,000
	(1429mm)	(438mm)	(1038mm)	(1016mm)	(381mm)	

MATERIAL:

- Drop Plenum Steel
- Drum Diffuser
 - Steel frame and drum interior
 - Aluminum blades and drum exterior
- Steel hardware

DROP PLENUM CONSTRUCTION:

- Acoustically perforated flow pyramid
- · Bottom and sides acoustically insulated
- Inlet
 - □ Standard Inlet
 - □ FLNG Inlet with 1 1/2" (38mm) flange
- Integral corner hanger brackets
- Corner plate (shipped loose) with 1/2" (13mm) hole for installation with threaded rod

ALL METRIC DIMENSIONS () ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER

PROJECT:

BY

CUSTOMER:

CUSTOMER:

SPEC. SYMBOL:

DBH

DROP BOX
WITH HCD DRUM DIFFUSERS

2023-11-15



DBH - Drop Box with HCD Drum Diffusers

DROP DIFFUSER CONSTRUCTION:


- 4W 4-way air discharge pattern
- 1B Single row of blades
- Blades are individually adjustable
- Drum can be rotated 30° in either direction
- Detents on the frame hold the drum in the desired location


FINISH:


- Drop Plenum
 - □ PL-GALV Mill Galvanized
 - □ PL-B12 Standard White
- Drum Diffuser
 - □ B12 Standard White

NOTES:

- Dimensions A and B are nominal sizes
- Factory tolerance ±1/8" (3mm)







ALL METRIC DIMENSIONS () ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER

PROJECT:

ENGINEER:

CUSTOMER:

SUBMITTAL DATE:

SPEC. SYMBOL:

DBH

DROP BOX
WITH HCD DRUM DIFFUSERS

2023-11-15