



UNIT SIZE	INLET	WIDTH W	LENGTH	
	W1		L	B
9	10 (254)	17 1/2 (445)	20 1/8 (511)	3 13/16 (97)
10	12 (305)			
12	16 (406)	24 (610)	23 5/8 (600)	5 5/16 (136)
14	21 (533)	30 (762)		
16	29 (737)	38 (965)		

**STANDARD CONSTRUCTION:**

- 1/2" (13mm) THICK INTERNAL FIBERGLASS INSULATION WHICH MEETS REQUIREMENTS OF NFPA 90A AND UL181.
- 22 GAUGE GALVANIZED STEEL HOUSING. MECHANICALLY SEALED, LEAK RESISTANT CONSTRUCTION.
- RECTANGULAR DISCHARGE OPENING WITH SLIP AND DRIVE CLEAT DUCT CONNECTION.
- MULTI-POINT, CENTER AVERAGING AIRFLOW SENSOR.
- 1/2" (13mm) GALVANIZED DAMPER SHAFT WITH POSITION INDICATOR.
- RIGHT HAND UNIT SHOWN (CRH), LEFT HAND AVAILABLE.

**CONTROLS OPTIONS:**

- ☐ FIELD MOUNTED CONTROLS, SUPPLIED BY OTHERS (FLD)
- ☐ FACTORY MOUNTED DIGITAL CONTROLS, SUPPLIED BY OTHERS (FAC)

**CONTROLS SUPPLIED AND MOUNTED BY PRICE (EHP):**

- ☐ DIGITAL CONTROLS (DIG)
- ☐ PNEUMATIC CONTROLS (PNEU)

**UNIT OPTIONS:**

- ☐ NEMA1 CONTROLS ENCLOSURE (PS)
- ☐ DISCONNECT SWITCH (DSW)
- ☐ 20 GAUGE CASING (20GA)
- ☐ HANGER BRACKETS (HB)
- ☐ BRASS AIRFLOW SENSOR GAUGE TAPS (GT)

**BOTTOM ACCESS DOOR:**

- ☐ ACCESS DOOR WITH SCREWS (AD)
- ☐ ACCESS DOOR WITH SNAP LATCHES (ADL)
- ☐ ACCESS DOOR WITH QUARTER TURN LATCHES (ADQ)

**LINER OPTIONS:**

- ☐ FIBER FREE FOAM 1/2" (13mm) (FF50)
- ☐ FOIL FACED FIBERGLASS BOARD 5/8" (16mm) (FB)
- ☐ SOLID METAL WITH FG50 (SM50)
- ☐ CLEANROOM ANGLES WITH FB (CRAF)
- ☐ PERFORATED METAL WITH FB (AFPM)



ALL METRIC DIMENSIONS ( ) ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

<b>PROJECT:</b>		 <b>SDVLP</b> <b>SINGLE DUCT TERMINAL</b> <b>VARIABLE VOLUME</b> <b>LOW PROFILE</b>
<b>ENGINEER:</b>		
<b>CUSTOMER:</b>		
<b>SUBMITTAL DATE:</b>	<b>SPEC. SYMBOL:</b>	
		CH 274048 06/06/2022