



**MATERIAL:**

- PHC
  - PERFORATED FACE: STEEL CONSTRUCTION
  - MOUNTING FRAME: EXTRUDED ALUMINUM CONSTRUCTION
  - #80 CORE: .5X.5X.5 ALUMINUM CONSTRUCTION
- APHC
  - PERFORATED FACE: ALUMINUM PERFORATED
  - MOUNTING FRAME: ALUMINUM
  - #80 CORE: .5X.5X.5 ALUMINUM
- PHCSS
  - PERFORATED FACE AND MOUNTING FRAME: 304 STAINLESS STEEL CONSTRUCTION
  - #80 CORE: .5X.5X.5 ALUMINUM

**FINISH:**

- PHC, APHC: MOUNTING FRAME, FACE AND CORE - B12 WHITE POWDER COAT
- PHCSS: #4 FINISH ON ALL EXPOSED SURFACES

**NOTE:**

- FACTORY TOLERANCE:  $\pm 1/32$ " (1)
- TYPE 'A' COUNTERSUNK SCREW MOUNTING WITH #8 S.M.S. PER FACTORY STANDARD.
- MAXIMUM SIZE ONE PIECE CONSTRUCTION IS 48"
- MINIMUM SIZE IS 24".

ALL METRIC DIMENSIONS ( ) ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

<b>PROJECT:</b>		<b>PRICE</b> <sup>®</sup>	
<b>ENGINEER:</b>			<b>PHC, APHC, PHCSS</b>
<b>CUSTOMER:</b>		231165	PERFORATED HIGH CAPACITY C/W DROP FACE
<b>SUBMITTAL DATE:</b>	<b>SPEC. SYMBOL:</b>	2010/11/29	5 1/2" & 9" NOM. WIDTH