
Submittal Sheet


LFGH - RC






FASTENING

☐ **A - COUNTERSUNK SCREW**



☐ **B - SPRING CLIP**



NOM. SIZE	LFG GRILLE SIZE	UNIT OVERALL			FACE FRAME		ROUGH OPENING
		A	B	C	G	H	
☐ 24 X 10 (610 X 254)	23 ¾ X 9 ¾ (603 X 248)	23 ⅞ (606)	9 ⅞ (251)	10 ⅜ (264)	25 ⅜ (645)	11 ⅜ (289)	24 X 10 (610 X 254)
☐ 48 X 10 (1219 X 254)	47 ¾ X 9 ¾ (1213 X 248)	47 ⅞ (1216)	9 ⅞ (251)	10 ⅜ (264)	49 ⅜ (1254)	11 ⅜ (289)	48 X 10 (1219 X 254)
☐ 72 X 10 (1829 X 254)	71 ¾ X 9 ¾ (1822 X 248)	71 ⅞ (1826)	9 ⅞ (251)	10 ⅜ (264)	73 ⅜ (1864)	11 ⅜ (289)	72 X 10 (1829 X 254)
☐ 96 X 10 (2438 X 254)	95 ¾ X 9 ¾ (2432 X 248)	95 ⅞ (2435)	9 ⅞ (251)	10 ⅜ (264)	97 ⅜ (2473)	11 ⅜ (289)	96 X 10 (2438 X 254)

GRILLE:
- EXTRUDED ALUMINUM CONSTRUCTION
- PRESSED CORE WITH REINFORCING SUPPORT BARS
- 1" FACE FRAME

PLENUM:
- STEEL CONSTRUCTION WITH BLACK FINISH
- DROP-IN INSTALLATION FROM ABOVE FLOOR

HYDRONIC ELEMENT:
- 1" NOM. (1.125" OD) COPPER TUBE
- FLARED CONNECTION
- 4" x 4" ALUMINUM FINS

ACOUSTIC LINER:
☐ 1/2" INTERNAL FIBER FREE INSULATION LINER (3LB DENSITY MIN.)

CONTROL:
☐ MASTER UNIT- TRANSFORMER INCLUDED FOR HOT WATER VALVE CONTROL
☐ DRONE UNIT

GRILLE FINISH:
☐ B11 - PURE WHITE
☐ B12 - WHITE - POWDER COAT
☐ B13 - OFF-WHITE - POWDER COAT
☐ B15 - ALUMINUM - POWDER COAT
☐ B17 - BLACK - POWDER COAT
☐ B25 - COLOR TO MATCH
☐ PC12 - PRIME COAT - POWDER COAT
☐ 66 - BRUSHED AND POWDER COAT CLEAR
☐ MILL - RAW ALUMINUM
☐ PA - PREPARED ALUMINUM MILL FINISH FACTORY CLEANED
☐ AB - ANODIZED BLACK
☐ AC - ANODIZED CLEAR
☐ ALB - ANODIZED LIGHT BRONZE
☐ AMB - ANODIZED MEDIUM BRONZE
☐ ADB - ANODIZED DARK BRONZE
☐ ASPL - ANODIZED COLOR OTHER THAN LISTED
☐ SPL - SPECIAL FINISHES

CORE OPTIONS:
- 1/4" ON CENTER SPACING
☐ 15A - 0° DEFLECTION - 3/32" BARS
☐ 16A - 15° DEFLECTION - 1/8" BARS
- 7/16" ON CENTER SPACING
☐ 25C - 0° DEFLECTION - 3/16" BARS
☐ 26C - 15° DEFLECTION - 3/16" BARS
☐ 27C - 30° DEFLECTION - 3/16" BARS

AIR PATTERN:
☐ DV1 - 1" (25) DIRECTIONAL VANES

ALL METRIC DIMENSIONS ( ) ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

PROJECT:		
ENGINEER:	GF	**LFGH - RC** **LINEAR FLOOR GRILLE** **HYDRONIC HEAT** **RECIRCULATION**
CUSTOMER:	253221	
SUBMITTAL DATE:	**SPEC. SYMBOL:**	2013/11/13


Solid Edge


© Copyright PRICE INDUSTRIES 2018

LFGH - RC

LFGH-RC CONTINUOUS:

LENGTHS > 96" ARE SUPPLIED IN SECTIONS TO BE ASSEMBLED ON-SITE.





ALL METRIC DIMENSIONS ( ) ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.


PROJECT:			
ENGINEER:		GF	**LFGH - RC** **LINEAR FLOOR GRILLE** **HYDRONIC HEAT** **RECIRCULATION**
CUSTOMER:		253221	
SUBMITTAL DATE:	**SPEC. SYMBOL:**	2013/11/13	


Solid Edge

© Copyright PRICE INDUSTRIES 2018

Submittal Sheet


LFGH - RC






FASTENING

☐ **A - COUNTERSUNK SCREW**



☐ **B - SPRING CLIP**



NOM. SIZE	LFG GRILLE SIZE	UNIT OVERALL A	UNIT OVERALL B	UNIT OVERALL C	FACE FRAME G	FACE FRAME H	ROUGH OPENING	HEAT OUTPUT (W)
☐ 24 X 10 (610 X 254)	23 ¾ X 9 ¾ (603 X 248)	23 ⅞ (606)	9 ⅞ (251)	10 ⅜ (264)	25 ⅜ (645)	11 ⅜ (289)	24 X 10 (610 X 254)	500
☐ 48 X 10 (1219 X 254)	47 ¾ X 9 ¾ (1213 X 248)	47 ⅞ (1216)	9 ⅞ (251)	10 ⅜ (264)	49 ⅜ (1254)	11 ⅜ (289)	48 X 10 (1219 X 254)	1000
☐ 72 X 10 (1829 X 254)	71 ¾ X 9 ¾ (1822 X 248)	71 ⅞ (1826)	9 ⅞ (251)	10 ⅜ (264)	73 ⅜ (1864)	11 ⅜ (289)	72 X 10 (1829 X 254)	1500
☐ 96 X 10 (2438 X 254)	95 ¾ X 9 ¾ (2432 X 248)	95 ⅞ (2435)	9 ⅞ (251)	10 ⅜ (264)	97 ⅜ (2473)	11 ⅜ (289)	96 X 10 (2438 X 254)	2000

GRILLE:
- EXTRUDED ALUMINUM CONSTRUCTION
- PRESSED CORE WITH REINFORCING SUPPORT BARS
- 1" FACE FRAME

PLENUM:
- STEEL CONSTRUCTION WITH BLACK FINISH
- DROP-IN INSTALLATION FROM ABOVE FLOOR

HEATER ELEMENT:
☐120/1/60 ELECTRICAL
☐ 240/1/60 ELECTRICAL
☐ 277/1/60 ELECTRICAL
- FINNED STRIP HEATER, MULTIPLE ELEMENTS MAY BE SUPPLIED ON LONGER UNITS
- TRANSFORMERS INCLUDED

ACOUSTIC LINER:
☐ 1/2" INTERNAL FIBER FREE INSULATION LINER (3LB DENSITY MIN.)

GRILLE FINISH:
☐ B11 - PURE WHITE
☐ B12 - WHITE - POWDER COAT
☐ B13 - OFF-WHITE - POWDER COAT
☐ B15 - ALUMINUM - POWDER COAT
☐ B17 - BLACK - POWDER COAT
☐ B25 - COLOR TO MATCH
☐ PC12 - PRIME COAT - POWDER COAT
☐ 66 - BRUSHED AND POWDER COAT CLEAR
☐ MILL - RAW ALUMINUM
☐ PA - PREPARED ALUMINUM MILL FINISH FACTORY CLEANED
☐ AB - ANODIZED BLACK
☐ AC - ANODIZED CLEAR
☐ ALB - ANODIZED LIGHT BRONZE
☐ AMB - ANODIZED MEDIUM BRONZE
☐ ADB - ANODIZED DARK BRONZE
☐ ASPL - ANODIZED COLOR OTHER THAN LISTED
☐ SPL - SPECIAL FINISHES

CORE OPTIONS:
- 1/4" ON CENTER SPACING
  - ☐ 15A - 0°DEFLECTION - 3/32" BARS
  - ☐ 16A - 15° DEFLECTION - 1/8" BARS
- 7/16" ON CENTER SPACING
  - ☐ 25C - 0° DEFLECTION - 3/16" BARS
  - ☐ 26C - 15° DEFLECTION - 3/16" BARS
  - ☐ 27C - 30° DEFLECTION - 3/16" BARS

AIR PATTERN:
☐ DV1 - 1" (25) DIRECTIONAL VANES

ALL METRIC DIMENSIONS ( ) ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

PROJECT:		price
ENGINEER:	DS	**LFGH - RC**
CUSTOMER:	**258474**	**LINEAR FLOOR GRILLE ELECTRI C HEAT RECIRCULATION**
SUBMITTAL DATE: / **SPEC. SYMBOL:**	2013/11/13	


Solid Edge


© Copyright PRICE INDUSTRIES 2013

LFGH - RC

LFGH-RC CONTINUOUS:

LENGTHS > 96" ARE SUPPLIED IN SECTIONS TO BE ASSEMBLED ON-SITE.





ALL METRIC DIMENSIONS ( ) ARE SOFT CONVERTED. IMPERIAL DIMENSIONS ARE CONVERTED TO METRIC AND ROUNDED TO THE NEAREST MILLIMETER.

PROJECT:			**LFGH - RC** **LINEAR FLOOR GRILLE ELECTRI C HEAT RECIRCULATION**
ENGINEER:		DS	
CUSTOMER:		258474	
SUBMITTAL DATE:	**SPEC. SYMBOL:**	2013/11/13	

Solid Edge

© Copyright PRICE INDUSTRIES 2013