


Spotlight

The Spotlight enables precise, target-oriented illumination. The 90° hinged base combined with a full 360° rotation allows for a high degree of flexibility in orientation. There are options for narrow, medium and wide beam angles. The light can be used in a variety of applications including offices, hospitality or lobby spaces. Used in combination with the Node Multisensor, these lights are capable of dimming in response to daylight, space use, wall switch or network command.



Product Features

- Modular mechanical and electrical connection to the Node system
- Dimmable from 0%, 5-100%
- Easy to install
- Easy to maintain
- Instant full light
- EEL Rating: A+
- L70 Lumen Maintenance: 50,000 hours

Specifications

Mounting Style	Diameter	Dimension A	Dimension B	Weight
Recessed Channel Mount	90 mm/3.54 in.	58 mm/2.28 in.	67 mm/2.64 in.	516 g/1.16 lb
Trimless	90 mm/3.54 in.	40 mm/1.58 in.	67 mm/2.64 in.	509 g/1.12 lb
Surface Mount	90 mm/3.54 in.	40 mm/1.58 in.	67 mm/2.64 in.	509 g/1.12 lb
Flush Channel Mount	90 mm/3.54 in.	58 mm/2.28 in.*	67 mm/2.64 in.	516 g/1.14 lb

*58mm will be above ceiling plane.

Beam Width	Luminaire Power	Maximum Current	Nominal Voltage	Luminaire Flux	Source Flux	Maximum Value	Efficacy
Narrow (13°)	19.0 W	550 mA	36 V	1913 lm	1913 lm	8226 cd/klm	101 lm/W
Medium (24°)	19.0 W	550 mA	36 V	1759 lm	1759 lm	3096 cd/klm	93 lm/W
Wide (48°)	19.0 W	550 mA	36 V	1903 lm	1903 lm	1403 cd/klm	100 lm/W
Extra Wide (67°)	19.0 W	550 mA	36 V	1784 lm	1784 lm	891 cd/klm	94 lm/W

Adjustability

- 360° rotation, 90° angle

Color Temperature

- 3000K
- 3500K
- 4000K

CRI

- 90

Certification

- CE (Europe)
- ETL (USA)
- CSA (Canada)

Construction

- Housing material: Aluminium

Lamp Type

- LED

Energy Consumption


- 20.90 kWh/1000h

Driver


- Sold separately

Polar Curves


Narrow



Medium



Wide



Extra Wide

