
Downlight

The Downlight enables target-orientated illumination. The light can be used in a variety of applications including offices, hospitality or lobby spaces. Used in combination with the Node Multisensor, these Downlights are capable of dimming in response to daylight, space use, wall switch or network command.



Product Features

- Modular mechanical and electrical connection to the Node system
- Dimmable from 0%, 5-100%
- Easy to install
- Easy to maintain
- Instant full light
- EEI Rating: A+
- L70 Lumen Maintenance: 50,000 hours

Specifications

Mounting Style	Diameter	Height
Flush Channel	90 mm/3.5 in.	75 mm/3.0 in.
Recessed Channel	90 mm/3.5 in.	75 mm/3.0 in.
Trimless	90 mm/3.5 in.	165 mm/6.5 in.

Beam Width	Luminaire Power	Maximum Current	Nominal Voltage	Luminaire Flux	Source Flux	Maximum Value	Efficacy
Narrow (13°)	19.0 W	550 mA	36 V	1913 lm	1913 lm	8226 cd/klm	101 lm/W
Medium (24°)	19.0 W	550 mA	36 V	1759 lm	1759 lm	3096 cd/klm	93 lm/W
Wide (48°)	19.0 W	550 mA	36 V	1903 lm	1903 lm	1403 cd/klm	100 lm/W
Extra Wide (67°)	19.0 W	550 mA	36 V	1784 lm	1784 lm	891 cd/klm	94 lm/W

Color Temperature/CCT

- 3000K
- 3500K
- 4000K

CRI

- 90

Certification

- CE (Europe)
- ETL (USA)
- CSA (Canada)

Construction

- Housing material: Aluminium

Lamp Type

- LED

Energy Consumption


- 20.90 kWh/1000h

Driver


- Sold separately

Polar Curves


Narrow



Medium



Wide



Extra Wide

